Tel: 0381 – 235 5751 e-mail : itdept-tr@nic.in

## GOVERNMENT OF TRIPURA DIRECTORATE OF INFORMATION TECHNOLOGY

ITI Road, Indranagar, Agartala - 799006

F. No. 5(69)/DIT/AUT/2024/2474

Dated: 30/06/2025

## SHORT NOTICE INVITING QUOTATION (SNIO)

Sealed quotations are hereby invited from experienced and resourceful contractors/suppliers for execution of the following work under the Directorate of Information Technology, Government of Tripura.

Scope of Work: The details of work is attached in Annexure - A

## Terms & Conditions:

1. Interested agencies / quotationer submit their rate quotations specifying taxes etc.

2. Interest bidders should submit the Notice Inviting Quotation reference no & date with their respective reference no. & date.

3. Last date of submission of rate quotation is on or before 08/07/2025 upto 2 PM along with the following documents.

- 4. GSTN registration No.
- 5. Photo copy of PAN card.
- 6. Copy of enlisted license PWD/CPWD etc.
- 7. DIT reserves the right to accept or reject, in full or in part, any or all the offers without assigning any reason whatsoever. DIT does not bind itself to accept the lowest on any bid and reserves the right to reject all or any bid or cancel the SNIQ without the vendor having the right to object to such re-issue.

(Jeya Ragul Geshan B., IFS)

Director, IT,

Govt. of Tripura

No	SOR	Description of Item	Unit	No		L	В	H/D	QTY	Amount
	DOR	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to					-	,5	4,,	·············
1	==	IS: 733 and IS 1285, fixing with dash fasteners of required dia and size, including necessary filling up of gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc.  Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever							0	
		required including cleat angle, aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawing and the direction of Engineerincharge. (Glazing and pancling and dash fasteners to be paid for separately):								u va
a	16.1.1.3	For fixed portion of approved quality: Polyester powder coated aluminium ( minimum thickness of polyester powder coating of 50 micron ).	-							
		5th Floor			_					
		Horizental		2	4	1.7	13.6			
		Vertical		2	3	2.43	14.58	J.P		
		1.924kg/meter		1			28.18	2.15	60.587	
		Ground Floor						1		
		Horizental		2	4	2.74	21.92			
		Vertical		2	4	2.43	19.44		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
		1.924kg/meter					41.36	2.15	88.924	
			kg						149.511	
b		For shutters of doors, windows & ventilators including providing and fixing hinges / pivots and making provision for fixing fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately):	· .		Y					
	16.1.2.3	Polyester powder coated aluminium ( minimum thickness of polyester powder coating of 50 micron ).		4-						
		Door Vertical		1	2	2.01	4.02	2.05	8.241	
		Door top /Middel/Bottom		1	3	0.9	2.7	2.646	7.144	
			kg						15.385	
2	16.3.1	Providing and fixing of glazing of approved quality in aluminium doors, windows, ventilator, shutters and partition etc. with EPDM rubber / neoprene gasket etc. complete as per architectural drawing and the direction of Engineer-in-charge (Cost of snap beading shall be paid in basic item): With float glass panes of 5.5 mm thickness (weight not less than 13.75 kg / sqm)								
		5th Floor		2	2	0.83	0.81		2.69	
	,			2	2	0.53	0.81	1	1.72	
_			sqm					17	4.41	
3	16.25.3	Aluminium Composite Panels of 4mm total thickness with Top coil– 0.50mm AA3003 / AA3105 / AA5005 Grade, manufactured as per IS-737 1986, FR Grade Class A2+ with 3mm Aluminium Corrugated Core as per standard EN 13501-1, class A2, and Bottom coil 0.50mm AA3003 / AA3105 / AA5005 Grade manufactured as per IS-737 1986 with minimum 25 microns lead free PVDF Coating conforming to AAMA2605 on top coil and Service coating on Back Coil (4 - 6 microns) having minimum								
		panel weight of 4 Kg/m2								
		5th Floor		2	2	0.85	0.81		2.75	
				2	2	0.53	0.81	K	1.72	
		Ground Floor		3	3	0.91	0.91		7.45	

		Door		1	2	0.9	1.05	1 Na. 2	1 89	41
		D001	sqm	1					13.81	
4	16.12.3	Providing and fixing aluminium round shape handle of outer dia 100 mm with SS screws etc. of approved quality complete as per direction of Engineer-in-charge:  Polyester powder coated aluminium minimum thickness 50 micron.					,			
			each	2					2.00	
5	16.14	Providing and fixing 100 mm brass locks (best make of approved quality) with 6 levers without pair of handles for aluminium doors including necessary cutting and making good etc. complete as per direction of Engineerin-charge								-
	-	6 2ng	each	1					1.00	