Tel: 0381 – 235 5751 e-mail: itdept-tr@nic.in

GOVERNMENT OF TRIPURA DIRECTORATE OF INFORMATION TECHNOLOGY

ITI Road, Indranagar, Agartala - 799006

F. No. 5(69)/DIT/AUT/2024/13(5(1))

Dated: 20/03/2025

SHORT NOTICE INVITING QUOTATION (SNIQ)

Sealed quotations are hereby invited from experienced and resourceful contractors/suppliers for execution of the following work under the Directorate of Information Technology, Government of Tripura.

Scope of Work: The details of work is attached in Annexure - A

Terms & Conditions:

1. Interested agencies / quotationer submit their rate quotations specifying taxes etc.

2. Interest bidders should submit the Notice Inviting Quotation reference no & date with their respective reference no & date.

3. Last date of submission of rate quotation is on or before 26/03/2025 upto 2 PM along with the following documents.

4. GSTN registration No.

5. Photo copy of PAN card.

6. Copy of enlisted license PWD/CPWD etc.

7. DIT reserves the right to accept or reject, in full or in part, any or all the offers without assigning any reason whatsoever. DIT does not bind itself to accept the lowest on any bid and reserves the right to reject all or any bid or cancel the SNIQ without the vendor having the right to object to such re-issue.

(Jeya Ragul Geshan B., IFS)

Director, IT,

Govt. of Tripura

Annexure - A

						Annexure - A							
No	SOR	Description of Item	Unit	N	o	L	В	H/D	QTY	Amount			
1	,	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up of gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawing and the direction of Engineerincharge. (Glazing and paneling and dash fasteners to be paid for separately):											
а	16.1.1.3	For fixed portion of approved quality: Polyester powder coated aluminium (minimum thickness of polyester powder coating of 50 micron).				A .							
-		2nd floor (89x32x2.75)mm				4							
		Horizental		1	4	5.18	20.7						
		Vertical	1	1	7	2.43	17						
		Horizental		1	4	4.75	19			`			
		Vertical	1	1	6	2.43	14.6						
-		Horizental	1	1	4	4.57	18.3						
		Vertical		1	5	2.43	12.2						
		2.150kg/meter	1				102	2.15	218.741				
			kg				1		218.741				
b		For shutters of doors, windows & ventilators including providing and fixing hinges / pivots and making provision for fixing fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately):		-	2			SP	0.1				
2	16.3.1	Providing and fixing of glazing of approved quality in aluminium doors, windows, ventilator, shutters and partition etc. with EPDM rubber / neoprene gasket etc. complete as per architectural drawing and the direction of Engineer-in-charge (Cost of snap beading shall be paid in basic item): With float glass panes of 5.5 mm thickness (weight not less than 13.75 kg / sqm)			u.				-				
		2nd floor	I	2	6	0.86	0.81		8.36				
				2	5	0.95	0.81		7.70				
				2	5	0.91	0.81		7.37				
			sqm				945		23.43				
3	16.25.3	Aluminium Composite Panels of 4mm total thickness with Top coil—0.50mm AA3003 / AA3105 / AA5005 Grade , manufactured as per IS-737 1986, FR Grade Class A2+ with 3mm Aluminium Corrugated Core as per standard EN 13501-1, class A2, and Bottom coil 0.50mm AA3003 / AA3105 / AA5005 Grade manufactured as per IS-737 1986 with minimum 25 microns lead free PVDF Coating conforming to AAMA2605 on top coil and Service coating on Back Coil (4 - 6 microns) having minimum panel weight of 4 Kg/m2											
		2nd floor		1	6	0.86	0.81		4.18				
		Door		1	2	0.9	1.05		1.89				
			sqm						6.07				
-			each	1		1			1.00				